

MICRO-TUFLOK®

The Micro-Tuflok is an one-piece fastener that is quickly installed by hand or with automatic equipment. It is ideally suited for fastening of electronic components to surface mounted printed circuit boards and is removable and reusable.



| PART NUMBER | HOLE DIAMETER | PANEL RANGE | PARTS DIMENSIONS | | | | SPECIAL FEATURES |
|-------------|---------------|-------------|------------------|------|------|------|------------------|
| | | | A | B | C | D | |
| 1700-00 | .097-.103 | .160-.180 | .040 | .190 | .060 | .345 | — |
| 1701-00 | .097-.103 | .290-.310 | .045 | .190 | .060 | .475 | — |
| 1702-00 | .106-.112 | .080-.105 | .050 | .218 | .060 | .300 | Retaining Ring |
| 1706-00 | .122-.128 | .105-.130 | .050 | .218 | .060 | .320 | — |
| 1707-00 | .122-.128 | .130-.155 | .050 | .218 | .060 | .345 | — |
| 1703-00 | .122-.128 | .155-.180 | .040 | .218 | .060 | .370 | — |
| 1704-00 | .122-.128 | .240-.265 | .040 | .218 | .060 | .455 | — |
| 1708-00 | .144-.154 | .265-.290 | .050 | .300 | .060 | .470 | .165 Shoulder |
| 1709-00 | .153-.163 | .205-.230 | .060 | .297 | .060 | .415 | .177 Shoulder |

NOTE: Dimensions listed are nominal.